

INLAND WATERS – List of Lights, Buoys and Fog Signals

No.	Name	Position ----- Latitude N. Longitude W.	Light Characteristics	Focal Height in m. above water	Nominal Range	Description ----- Height in meters above ground	Remarks ----- Fog Signals
-----	------	--	--------------------------	--	------------------	--	---------------------------------

WELLAND CANAL

Port Weller										
551.06	Port Weller Outer	On outer end of W. breakwater. 43 14 41.2 79 13 02.9	Iso	R	4s	15.2	9	Red skeleton tower on white building. 12.3	Seasonal.	Chart:2042 Edn 08/12(B12-020)
551.07	Port Weller East Breakwater	43 14 41.1 79 12 56.6	Fl	G	4s	8.0	5	White mast, green upper portion. 7.2	Seasonal.	Chart:2042
551.08	Lighted spar buoy WC1	43 14 31.3 79 12 57.2	Fl	G	4s	Green spar, marked "WC1".	Seasonal. (In place Year round.)	Chart:2042
551.09	Lighted spar buoy WC2	43 14 31.4 79 13 03.2	Fl	R	4s	Red spar, marked "WC2".	Seasonal. (In place Year round.)	Chart:2042 Edn 07/12
551.11	Lighted spar buoy WC7	43 14 01.7 79 12 57.5	Fl	G	4s	Green spar, marked "WC7".	Seasonal. (In place Year round.)	Chart:2042
551.12	Lighted spar buoy WC8	43 14 01.7 79 13 04.4	Fl	R	4s	Red spar, marked "WC8".	Seasonal. (In place Year round.)	Chart:2042
551.13	Welland Canal (Mile 0.7) Downbound Steering	43 13 55.8 79 13 08.7	Iso	Y	2s	10.0	Mast, orange triangular daymark. 9.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042
551.14	Welland Canal (Mile 1.2)	43 13 33.1 79 12 56.9	F	W	9.0	Mast. 8.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042
551.16	Port Weller range	Welland Canal entrance. 43 13 23.5 79 12 59.7	Iso	Y	2s	16.5	Orange and white mast. 9.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	
551.17		180° 906.8m from front.	F	R Y G	32.0	Orange and white skeleton tower. 15.0	Red from 177°30' to 179°40'; yellow from 179°40' through S. to 180°20'; green from 180°20' to 182°30'. Yellow sector indicates preferred channel. Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042
551.18	Lighted spar buoy WC9	43 12 33.4 79 12 34.9	Fl	G	4s	Green spar, marked "WC9".	Seasonal. (In place Year round.)	Chart:2042

INLAND WATERS – List of Lights, Buoys and Fog Signals

No.	Name	Position		Light Characteristics			Focal Height in m. above water	Nominal Range	Description		Remarks	
		Latitude N.	Longitude W.							Height in meters above ground		Fog Signals
WELLAND CANAL												
551.19	Welland Canal (Mile 2.3)	43 12 21.6 79 12 28.6	F	W	9.0	Mast.	8.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042	
551.21	Lighted spar buoy WC11	43 12 01.8 79 12 22.3	Fl	G	4s	Green spar, marked "WC11".		Seasonal. (In place Year round.)	Chart:2042	
551.22	Welland Canal (Mile 3.3) Steering	43 11 27.3 79 11 54.2	Iso	Y	2s	10.0	Mast, orange triangular daymark.	9.0	Flashing Red (Occasional). Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042	
551.23	Lighted spar buoy WC13	43 11 13.4 79 11 52.3	Fl	G	4s	Green spar, marked "WC13".		Seasonal. (In place Year round.)	Chart:2042	
551.24	Lighted spar buoy WC17	43 11 00.4 79 11 47.3	Fl	G	4s	Green spar, marked "WC17".		Seasonal. (In place Year round.)	Chart:2042	
551.26	Lighted spar buoy WC19	43 10 47.9 79 11 46.2	Fl	G	4s	Green spar, marked "WC19".		Seasonal. (In place Year round.)	Chart:2042	
551.27	Lighted spar buoy WC21	43 10 22.3 79 11 42.8	Fl	G	4s	Green spar, marked "WC21".		Seasonal. (In place Year round.)	Chart:2042	
551.28	Lighted spar buoy WC23	43 10 13.1 79 11 42.5	Fl	G	4s	Green spar, marked "WC23".		Seasonal. (In place Year round.)	Chart:2042	
551.29	Welland Canal (Mile 6.2) Downbound Steering	43 08 40.9 79 11 28.9	Iso	Y	2s	10.0	Mast, orange triangular daymark.	9.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042	
551.31	Welland Canal (Mile 8.1) Industrial N.E.	43 06 46 79 11 36.1	Fl	W	4s	4.0	4	Mast.	1.0	Seasonal.	Chart:2042	
551.32	Welland Canal (Mile 8.1) Industrial W.	43 06 46 79 11 43.6	Fl	W	4s	4.0	4	Mast.	1.0	Seasonal.	Chart:2042	
551.33	Lighted spar buoy WC31	43 06 40.5 79 11 50.2	Fl	G	4s	Green spar, marked "WC31".		Seasonal. (In place Year round.)	Chart:2042	
551.34	Lighted spar buoy WC33	43 06 29.2 79 11 57.2	Fl	G	4s	Green spar, marked "WC33".		Seasonal. (In place Year round.)	Chart:2042	

INLAND WATERS – List of Lights, Buoys and Fog Signals

No.	Name	Position		Light Characteristics		Focal Height in m. above water	Nominal Range	Description		Remarks
		Latitude N.	Longitude W.					Height in meters above ground	Fog Signals	
WELLAND CANAL										
551.36	Welland Canal (Mile 9.2) Downbound Steering	43 05 47.9 79 12 26.2	Iso Y 2s	10.0	Mast, orange triangular daymark. 9.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042		
551.37	Welland Canal (Mile 9.5) Upbound Steering	43 05 35 79 12 31	Iso Y 2s	10.0	Mast, orange triangular daymark. 9.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042		
551.38	Welland Canal (Mile 10.9)	43 04 01.2 79 12 40.5	Fl W 4s	4.1	4	Mast. 4.0	Seasonal.	Chart:2042		
551.39	<i>Lighted spar buoy WC37</i>	<i>43 03 40 79 12 42.3</i>	<i>Fl G 4s</i>	<i>Green spar, marked "WC37".</i>	<i>Seasonal. (In place Year round.)</i>	Chart:2042		
551.41	<i>Lighted spar buoy WC39</i>	<i>43 02 12 79 12 43.3</i>	<i>Fl G 4s</i>	<i>Green spar, marked "WC39".</i>	<i>Seasonal. (In place Year round.)</i>	Chart:2042		
551.42	Welland Canal (Mile 13.0)	43 01 58.4 79 12 51.1	F Y	6.0	Mast, orange triangular daymark. 5.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042		
551.43	<i>Lighted spar buoy WC40</i>	<i>43 01 58 79 12 46.5</i>	<i>Fl R 4s</i>	<i>Red spar, marked "WC40".</i>	<i>Seasonal. (In place Year round.)</i>	Chart:2042		
551.44	Welland Canal (Mile 13.6) Downbound Steering	43 01 18.2 79 12 39.7	Iso Y 2s	9.0	Mast, orange triangular daymark. 8.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042		
551.46	Welland Canal (Mile 14.3) Upbound Steering	43 00 43.5 79 12 42.7	Iso Y 2s	9.0	Mast, orange triangular daymark. 8.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042		
551.47	Welland Canal (Mile 15.6) Downbound Steering	42 59 25.5 79 12 57.7	Iso Y 2s	9.0	Mast, orange triangular daymark. 8.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042		
551.48	Welland Canal (Mile 16.2) Upbound Steering	42 58 46.6 79 13 09.1	Iso Y 2s	9.0	Mast, orange triangular daymark. 8.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042		
551.49	Welland Canal (Mile 18.7) Downbound Steering	42 56 28.3 79 14 11.8	Iso Y 2s	9.0	Mast, orange triangular daymark. 8.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal.	Chart:2042		

INLAND WATERS – List of Lights, Buoys and Fog Signals

No.	Name	Position ----- Latitude N. Longitude W.	Light Characteristics	Focal Height in m. above water	Nominal Range	Description ----- Height in meters above ground	Remarks ----- Fog Signals
WELLAND CANAL							
551.51	Welland Canal (Mile 19.6) Upbound Steering	42 55 35.4 79 14 28.6	Iso Y 2s	9.0	Mast, orange triangular daymark. 8.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal. Chart:2042
551.52	<i>Lighted spar buoy WC42</i>	42 55 33.7 79 14 27	Fl R 4s	Red spar, marked "WC42".	Seasonal. (In place Year round.) Chart:2042
551.53	Welland Canal (Mile 19.8)	42 55 22.7 79 14 32.6	F Y	6.0	Mast. 5.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal. Chart:2042
551.54	<i>Lighted spar buoy WC43</i>	42 55 06.9 79 14 28.6	Fl G 4s	Green spar, marked "WC43".	Seasonal. (In place Year round.) Chart:2042
551.56	Welland Canal (Mile 20.8)	42 54 22.6 79 14 42.1	F Y	6.0	Mast. 5.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal. Chart:2042
551.57	Welland Canal (Mile 21.9)	42 53 15.1 79 14 56.5	F W	4.0	Mast. 5.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal. Chart:2042
551.58	Welland Canal (Mile 22.0)	42 53 08.4 79 14 56.6	F W	6.0	Mast. 5.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal. Chart:2042
551.59	Port Colborne Entrance range	42 52 40.9 079 14 52.3	F R	10.9	15 White cylindrical tower, orange triangular daymark, black vertical stripe. 7.4	Seasonal.
551.61		Wharf 16. 015°16' 471m from front.	F R	22	15 Skeleton tower, orange daymark with black stripe. 18.8	Seasonal. Chart:2042 Edn 10/16 (B16-006)
551.62	Wharf 17	Extreme S. end of wharf. 42 52 40 79 14 52.6	Fl Y 4s	3.0	2	Mast. 2.0	Maintained by St. Lawrence Seaway Management Corporation. Seasonal. Chart:2042
551.63	<i>Lighted spar buoy WC53</i>	42 52 30.1 79 14 55.1	Fl G 4s	Green spar, marked "WC53".	Seasonal. (In place Year round.) Chart:2042

INLAND WATERS – List of Lights, Buoys and Fog Signals

No.	Name	Position ----- Latitude N. Longitude W.	Light Characteristics	Focal Height in m. above water	Nominal Range	Description ----- Height in meters above ground	Remarks ----- Fog Signals
WELLAND CANAL							
551.64	<i>Lighted spar buoy WC55</i>	42 52 20.4 79 14 57.9	Fl G	4s	Green spar, marked "WC55".	Seasonal. (In place Year round.) Chart:2042
551.66	<i>Lighted spar buoy WC57</i>	42 52 11.2 79 15 00.6	Fl G	4s	Green spar, marked "WC57".	Seasonal. (In place Year round.) Chart:2042
551.67	<i>Lighted spar buoy WC59</i>	42 52 02.1 79 15 03.4	Fl G	4s	Green spar, marked "WC59".	Seasonal. (In place Year round.) Chart:2042
551.68	Port Colborne Inner	E. end of W. breakwater. 42 52 03.2 79 15 10.3	LFl W	10s	15.2	12 White square tower, red upper portion. 13.1	Seasonal. Chart:2042
551.69	Port Colborne Harbour	On weather station tower. 42 52 01.7 79 14 55	Iso Y	2s	9.8 Tower.	Visible from 178°45' to 180°45'. Maintained by St. Lawrence Seaway Management Corporation. Seasonal. Chart:2042
551.71	Port Colborne East Breakwater	On outer end of E. breakwater. 42 51 59.7 79 15 02.1	Fl G	4s	10.7	5 White cylindrical tower, green upper portion. 6.2	Seasonal. Chart:2042
551.72	Port Colborne Outer	On S. end of W. breakwater. 42 51 45.6 79 15 17.5	F R	11.0	7 White square tower, red upper portion. 7.7	Intensified over an arc of 030° SSW. Emergency light. Seasonal. Chart:2042
551.73	<i>Port Colborne lighted spar buoy E3</i>	<i>On E. side of entrance. 42 51 42.1 79 15 11.8</i>	<i>Fl G</i>	<i>4s</i>	<i>.....</i>	<i>Green spar, marked "E3".</i>	<i>Seasonal. (In place Year round.)</i> Chart:2042