

**PACIFIC COAST – List of Lights, Buoys and Fog Signals**

No.	Name	Position		Light Characteristics		Focal Height in m. above water	Nominal Range	Description		Remarks		
		Latitude N.	Longitude W.					Height in meters above ground	Fog Signals			
<b>ARROW LAKE - COLUMBIA RIVER</b>												
26	Syringa Creek	S. side of channel opposite creek. 49 20 18.8 117 52 49.7	FI	G	4s	12.8	4	Mast, green, white and black square daymark.	Year round.		<b>Chart:3056 Edn 04/11 Edn 12/15 (P15-088)</b>	
26.5	Tulip Point	E. of creek. 49 21 31.9 117 55 23.1	FI	R	4s	13.1	4	Mast.	Year round.		<b>Chart:3056 Edn 12/15 (P15-087)</b>	
27	Cayuse Creek	W. side of lake 49 23 31.8 118 01 02.5	FI	W	4s	12.4	6	Mast, green, white and black square daymark.	Year round.		<b>Chart:3056 Edn 04/11</b>	
27.2	Renata South	E. side of Lake. 49 26 12.7 118 04 46.7	FI	R	4s	11.2	4	White cylindrical tower, red band on top.	Radar reflector. Year round.		<b>Chart:3056</b>	
27.3	Renata North	Lower Arrow Lake. 49 26 58.3 118 05 22.3	FI	W	4s	11.5	5	Mast, red and white triangular daymark.	Year round.		<b>Chart:3056</b>	
27.5	Bowman Creek	W. side of lake 49 31 34 118 08 42.9	FI	W	4s	11.7	6	Mast, green, white and black square daymark.	Year round.		<b>Chart:3056 Edn 04/11</b>	
28	Snag Bay	W. side of lake. Arrow Lake 49 36 31.2 118 09 28.4	FI	W	4s	12.9	6	Mast, green, white and black square daymark.	Year round.		<b>Chart:3056 Edn 04/11</b>	
28.5	Johnston Creek East	E. side of lake. Arrow Lake 49 41 31.2 118 07 42.2	FI	W	4s	10.7	5	Mast, red and white triangular daymark.	Year round.		<b>Chart:3056</b>	
29	Edgewood East	E. side of lake. Arrow Lake 49 45 59.9 118 06 39.3	FI	W	4s	11.5	5	Mast, red and white triangular daymark.	Year round.		<b>Chart:3056</b>	
29.5	Needles Sector	W. side of channel at Andres Creek. 49 53 50.8 118 05 04.5	F	R W G	.....	11.7	7	Mast, red slatwork daymark, white vertical stripe.	Red from 003°30' to 009°15'; white from 009°15' to 010°15'; green from 010°15' to 017°30'. White sector indicates preferred channel. Year round.		<b>Chart:3056</b>	
30	Upper Whatshan Sector	W. side of channel, S. of power station. 49 54 00 118 04 41.8	F	G W R	.....	13.7	8	Mast, red slatwork daymark, white vertical stripe.	Green from 220°15' to 225°45'; white from 225°45' to 230°15'; red from 230°15' to 236°30'. White sector indicates preferred channel. Year round.		<b>Chart:3056</b>	
31	Whatshan Sector downstream	W. side of channel, N. of power station. 49 55 22.8 118 03 15.7	F	R W G	.....	10.1	7	Mast, red slatwork daymark, white vertical stripe.	Red from 010°45' to 016°30'; white from 016°30' to 021°30'; green from 021°30' to 027°30'. White sector indicates preferred channel. Year round.		<b>Chart:3056</b>	
31.5	Fern Creek	On W. side of channel, near Fern Creek 49 57 40 118 00 43	FI	G	4s	7.6	4	Mast, green, white and black square daymark.	Year round.		<b>Chart:3057 Edn 04/11</b>	

**PACIFIC COAST – List of Lights, Buoys and Fog Signals**

No.	Name	Position ----- Latitude N. Longitude W.	Light Characteristics	Focal Height in m. above water	Nominal Range	Description ----- Height in meters above ground	Remarks ----- Fog Signals
<b>ARROW LAKE - COLUMBIA RIVER</b>							
32.7	Burton Approach	49 58 46.8 117 55 18.9	Fl G	4s	13.9 4	Mast, green, white and black square daymark.	Year round.  <b>Chart:3057 Edn 04/11</b>
33	Burton West	W. side of channel. Arrow Lake 49 59 27.1 117 54 24.1	Fl W-R	4s	15.5 4	Mast, green, white and black square daymark.	Year round.  <b>Chart:3057 Edn 04/11</b>
33.5	Sand Island light buoy A18	E. side of channel marking sand bar. 50 02 02.4 117 54 42	Fl R	4s	..... ..	Red, marked "A18".	Year round.  <b>Chart:3057</b>
34	Alwen Creek	W. side of channel. Arrow Lake 50 05 02.4 117 56 18.6	Fl G	4s	21.7 4	Mast, green, white and black square daymark.	Year round.  <b>Chart:3057 Edn 04/11</b>
34.5	Arrow Park	Arrow Lake 50 06 36.6 117 54 04.7	Fl G	4s	10.2 4	Mast, green, white and black square daymark.	Year round.  <b>Chart:3057 Edn 04/11</b>
37	Dispatch Island Sector	50 07 57.9 117 48 36.1	F R W G  Fl R	.....   4s	13.0 5   13.3 4	Mast, red slatwork daymark, white vertical stripe, red and white triangular daymark.	Green from 165°35' to 174°35'; white from 174°35' to 175°35'; red from 175°35' to 183°35'. White sector indicates preferred channel. Year round.  <b>Chart:3057</b>
38.5	Smith Point	W. side of lake. 50 12 38.4 117 49 34.4	Fl W	4s	11.8 6	Mast, green, white and black square daymark.	Year round.  <b>Chart:3057 Edn 04/11</b>
39	Nakusp light buoy A26	50 14 09.7 117 49 29.8	Fl R	4s	.....	Red, marked "A26".	Year round.  <b>Chart:3057</b>
39.5	Cape Horn	E. side of lake . 50 20 42.7 117 53 39.7	Fl W	4s	24.9 6	Mast.	Year round.  <b>Chart:3057</b>
40	Ann Point	E. side of lake. 50 28 02.2 117 54 56.6	Fl W	4s	12.6 6	Mast, red and white triangular daymark.	Year round.  <b>Chart:3057</b>
40.5	Albert Point	E. side of lake. 50 35 29 117 54 43.3	Fl W	4s	10.9 6	Mast, red and white triangular daymark.	Year round.  <b>Chart:3057</b>
40.6	Bannock Point	50 37 54.9 117 55 15.8	Fl G	4s	13.1 4	Mast, green, white and black square daymark.	Year round.  <b>Chart:3057 Edn 04/11</b>
40.7	Arrowhead light buoy A29	N. end of channel. Arrow Lake 50 40 22.4 117 54 31	Fl G	4s	.....	Green, marked "A29".	Year round.  <b>Chart:3057</b>
41	Whiskey Point	Arrow Lake 50 42 21.6 117 49 22.3	Fl W	4s	11.3 5	Mast, green, white and black square daymark.	Year round.  <b>Chart:3057 Edn 04/11</b>