No.	Name	Position Latitude N. Longitude W.	Light Characteristics			Focal Height in m. above water	Nomi- nal Range	Description Height in meters above ground	Remarks Fog Signal			
VANCOUVER HARBOUR												
385.5	Vancouver Approach Cautionary light buoy QA	W. of Point Grey. 49 16 34.4 123 19 18.4	FI	Υ	4 s			Yellow, marked "QA".	Year round.			
	Racon (G) X & S Bands									Chart:3481		
386 G5426	Point Atkinson	N. point of entrance to Burrard Inlet. 49 19 49.4 123 15 52.9	FI(2)	W	5s	32.9	15	White hexagonal tower, red band at top with 6 buttresses.	Flash 0.25 s; eclipse 0 flash 0.25 s; eclipse 3. Year round.	.75 s;		
386.3 <i>G5426.8</i>	Spanish Banks No.2	Entrance to English Bay. 49 17 21.1 123 14 51.9	FI(2)	R	6s	6.7	5	White cylindrical tower, red band at top on 9-pile dolphin.	Flash 0.5 s; eclipse 1 s flash 0.5 s; eclipse 4 s Year round.	3 ;		
387	Point Grey light and bell buoy Q62	N. of point, entrance to harbour. 49 17 20.4 123 15 58.8	Q	R	1s			Red, marked "Q62".	Year round.	Chart:3481 Chart:3481		
387.01 <i>G5426.6</i>	Spanish Bank	49 17 12.9 123 13 34.8	FI	W	4s	6.9	6	White cylindrical tower, red band at top on 9-pile dolphin.	Year round.	Chart:3481		
387.2 G5427.2	English Bay Anchorage East	Seaward end of breakwater. 49 16 31.8 123 11 18.1	Q	Υ	1s	4.9	8	Mast on wharf railing.	Privately maintained. Edn 06/	Chart:3481 15 (P15-022)		
388	Burrard Inlet Cautionary light buoy QB Racon (K)	E. end of Traffic Lane Separator. 49 19 02.2 123 12 04.5	FI	Y	4 s			Yellow, marked "QB".	Year round.			
388.1	X & S Bands Kitsilano light buoy Q52	Entrance to False Creek. 49 16 53.4 123 08 58.7	Q	R	1s			Red, marked "Q52".	Year round.	Chart:3481		
388.6	English Bay Beach light buoy Q41	Entrance to False Creek. 49 17 06.7 123 08 55.5	Q	G	1s			Green, marked "Q41".	Year round.	Chart:3493		
388.9	Kitsilano Base West	NW. corner of Coast Guard wharf. 49 16 36 123 08 20.9	F	R		1.3		On Coast Guard wharf.	Year round.	Chart:3493 Chart:3493		

No.	Name	Position Latitude N. Longitude W.		Light acteristic	Focal Height in m. above water	nal	Description Height in meters above ground	Remarks Fog Signals				
	VANCOUVER HARBOUR											
389	Kitsilano Base	SW. approach to False Creek at end of floating breakwater. 49 16 33.8 123 08 17.5	FI	R 4s	4.3	3	1-pile dolphin.	Year round.				
390 <i>G5430</i>	False Creek Sector	On N. pier of Burrard Bridge. 49 16 32.7 123 08 10.6	F	R W G	6.3	11	Mast.	Chart:3493 Red from 128° to 131°; white from 131° to 132°; green from 132° to 135°. Year round.				
390.5	Ferguson Point West Cardinal light buoy QC	W. of point, N. end of English Bay. 49 18 12.4 123 10 00.7	Q(9)	W 18	ōs		Yellow, black and yellow, marked "QC".	Chart:3493 Year round.				
392 G5434	Prospect Point	Under bluff at point. 49 18 50.4 123 08 29.1	Iso	R 29	11.5	10	White tower, red band at top.	Chart:3493 In operation 24 hours. Year round. Chart:3493				
392.5 G5437	Lions Gate Bridge South Sector	49 18 53.1 123 08 20.7	F	R W G	63.3	14	On bridge.	Green from 303° to 304°; white from 304° to 306°; red from 306° to 307°. In operation 24 hours. Year round.				
393 <i>G543</i> 8	Lions Gate Bridge North Sector	49 18 57.2 123 08 16.9	F	R W G	63.3	14	On bridge.	Chart:3493 Green from 303° to 304°; white from 304° to 306°; red from 306° to 307°. In operation 24 hours. Year round.				
394 G5435	First Narrows	Entrance to First Narrows. 49 19 09.1 123 08 46.7	Iso	G 2s	s 7.5	7	White cylindrical tower, green band at top on 4-pile dolphin.	Chart:3493 Radar reflector. Year round.				
395	Calamity Point	49 18 45.2 123 07 39.6	FI	W 4s	5.1	9	White cylindrical tower, green band at top on 16-pile dolphin.	Chart:3493 Radar reflector. Year round.				
395.3	Calamity Shoal light buoy Q65	49 18 40.4 123 07 36.7	FI	G 4	s		Green, marked "Q65".	Chart:3493 Year round.				
403 G5448	Burnaby Shoal	On shoal. 49 17 54.4 123 06 38.4	Q	R 1s	9.8	10	White cylindrical tower, red band at top.	Chart:3493 Chart:3493 Edn 07/15 (P15-063)				
403.3	Coal Harbour Approach	E. of Deadman Island. 49 17 43.1 123 07 03.1	FI	Υ	5.3		Mast on top of large dolphin.	Privately maintained. Year round. Chart:3493				

No.	Name	Position Latitude N. Longitude W.	Light Characteristics	Focal Height in m. above water	Nomi- nal Range	Description Height in meters above ground	Remarks Fog Signals					
VANCOUVER HARBOUR												
403.5 G5455	Deadman Island	S. of island. 49 17 33.6 123 07 23.9	Q R 1s	6.7	4	White cylindrical tower, red band at top on 3-pile dolphin.	Radar reflector. Year round. Chart:3493					
404 G5456	Coal Harbour	49 17 36.5 123 07 32.7	FI R 4s	6.5	4	White cylindrical tower, red band at top on 9-pile dolphin.	Radar reflector. Year round.					
408.5 <i>G546</i> 5	Terminal Dock East	49 17 38.3 123 03 02.8	FI R 4s	2.4	7	Mast on pilings.	Year round.					
408.51	Second Narrows West Directional	49 17 37.4 123 02 45.6	F R	7.9	10	White square skeleton tower on 3-pile dolphin.	Chart:3493 Visible on a bearing of 266°. Year round.					
							Chart:3494 Edn 12/10 (P10-121)					
408.53 <i>G5468.33</i>	Second Narrows Highway Bridge (Southeast)	On bridge. 49 17 39.3 123 01 33.8	F W	60.3		On bridge.	Visible from E approach. Maintained by B.C. Ministry of Transportation and Highways. Year round.					
408.54 G5468.32	Second Narrows Highway Bridge (Southwest)	On bridge. 49 17 39.3 123 01 35.1	F W	60.3		On bridge.	Chart:3494 Visible from W approach. Maintained by B.C. Ministry of Transportation and Highways. Year round.					
100.55	Constant Name	On bridge	- W			On bridge	Chart:3494					
408.55 G5468.31	Second Narrows Highway Bridge East	On bridge. 49 17 40.9 123 01 34.1	F W			On bridge.	Center light located on bottom of span. Floodlight pointed down. Maintained by B.C. Ministry of Transportation and Highways. Year round.					
							Chart:3494					
408.6 G5468	Second Narrows Highway Bridge West	On bridge, bottom of span. 49 17 40.9 123 01 34.9	F W	45.2		On bridge.	Indicates centre of navigation channel as visible from W. approach. Center light located on bottom of span. Floodlight pointed down. Maintained by B.C. Ministry of Transportation and Highways. Year round.					
							Chart:3494					
408.7 G5468.3	Second Narrows Highway Bridge (Northeast)	On bridge, NE. at road level. 49 17 42.5 123 01 33.9	F W	60.3		On bridge.	Visible from E. approach. Maintained by B.C. Ministry of Transportation and Highways. Year round.					
							Chart:3494					
408.8 G5468.2	Second Narrows Highway Bridge (Northwest)	W. side of bridge. 49 17 42.5 123 01 35.2	F W	60.3		On bridge.	Visible from W. approach. Maintained by B.C. Ministry of Transportation and Highways. Year round.					
							Chart:3494					

Chart:3494

No.	Name	Position Latitude N. Longitude W.	Light Characteristics						Nomi- nal Range	Description Height in meters above ground	Remarks Fog Signals	
VANCOUVER HARBOUR												
409	CN Railway Bridge Northeast	On bridge abutment. 49 17 43.3 123 01 27.6	F	G		4.9	5	On bridge.	Visible from E. approach. Year round.			
409.1	CN Railway Bridge Southeast	On bridge abutment. 49 17 38.6 123 01 27.8	F	R		4.9	4	On bridge.	Chart:3494 Visible from E. approach. Year round.			
409.2	CN Railway Bridge Southwest	On bridge abutment. 49 17 38.6 123 01 28.7	F	R		4.9	4	On bridge.	Chart:3494 Visible from W. approach. Year round.			
409.3	CN Railway Bridge Northwest	On bridge abutment. 49 17 43.3 123 01 28.6	F	G		4.9	5	On bridge.	Chart:3494 Visible from W. approach. Year round.			
409.35	CN Railway Bridge Sector	Second Narrows rail bridge. 49 17 40.9 123 01 27.9	F Al GW Al RW	R W G			10	On bridge.	Chart:3494 Green from 263° to 264°; Al GW from 264° to 265°; white from 265° to 267°; Al RW from 267° to 268°; red from 268° to 270°. White sector indicates preferred channel. Year round.			
									Chart:3494 Edn 12/10 (P10-122)			
409.4	CN Railway Bridge Centre Span Northeast	On bridge. 49 17 41 123 01 27.9	F Q	R R	 1s			On bridge.	Visible from E. approach. Privately maintained. Characteristics of light: Fixed or flashing (Occasional). Year round.			
									Chart:3494			
409.5	CN Railway Bridge Centre Span Northwest	On bridge. 49 17 41.1 123 01 28.5	F Q	R R	 1s			On bridge.	Visible from W. approach. Privately maintained. Characteristics of light: Fixed or flashing (Occasional). Year round.			
									Chart:3494			
409.6	CN Railway Bridge Centre Span East	On bridge. 49 17 40.9 123 01 27.9	F Q	G G	 1s			On bridge.	Indicates that span is raised. Visible from E. approach. Privately maintained. Characteristics of light: Fixed or flashing (Occasional). Year round.			
									Chart:3494			
409.7	CN Railway Bridge Centre Span West	On bridge. 49 17 41 123 01 28.5	F Q	G G	 1s			On bridge.	Indicates that span is raised. Visible from W. approach. Privately maintained. Characteristics of light: Fixed or flashing (Occasional). Year round. Chart:3494			

Chart:3494

No.	Name	Position Latitude N. Longitude W.	Light Characteristics		Focal Height in m. above water	Nomi- nal Range	Description Height in meters above ground	Remarks Fog Signals				
VANCOUVER HARBOUR												
409.8	CN Railway Bridge Centre Span Southeast	On bridge. 49 17 40.8 123 01 28.9	F Q	R R 1s			On bridge.	Visible from E. approach. Privately maintained. Characteristics of light: Fixed or flashing (Occasional). Year round.				
409.9	CN Railway Bridge Centre Span Southwest	On bridge. 49 17 40.8 123 01 28.5	F Q	R R 1s			On bridge.	Chart:3494 Visible from W. approach. Privately maintained. Characteristics of light: Fixed or flashing (Occasional). Year round.				
409.95	Riverside East	49 17 45.5 123 01 04.6	FI	G 4s	8.3	7	White square skeleton tower, green band at top on 6-pile dolphin.	Chart:3494 Year round. Chart:3494 Edn 12/10 (P10-123)				
410 <i>G547</i> 3	Second Narrows	E. of railway bridge. 49 17 46.4 123 00 36	Q	G 1s	8.1	6	White square skeleton tower, green band at top on 3-pile dolphin.	Year round. Chart:3494 Edn 12/10 (P10-124)				
410.5 <i>G5473.4</i>	Second Narrows East	NW. of Berry Point. 49 17 56.1 122 59 47.7	FI	G 4s	3.3	7	On centre pile of 19-pile dolphin.	Radar reflector. Year round. Chart:3494				
411 G5474	Berry Point	On N. extremity of point. 49 17 43.1 122 59 13.1	FI	R 4s	9.0	8	Triangular skeleton tower on 9-pile dolphin.	Edn 12/10 (P10-125) Year round. Chart:3494 Edn 04/11 (P11-005)				
412 <i>G547</i> 6	Roche Point	On S. extremity of point.	FI	W 4s	7.5	4	White cylindrical tower on 3-pile dolphin.	Year round.				
412.3 G5481	Woodlands	N. side of Indian Arm. 49 20 28.2 122 55 10.1	FI	G 4s	4.2	4	White cylindrical tower, green band at top.	Chart:3495 Radar reflector. Year round.				
412.4 G5481.2	Twin Islands	49 21 03.3 122 53 26.4	FI	R 4s	8.9	5	White tower, red band at top.	Chart:3495 Radar reflector. Year round.				
412.5 G5481.4	Best Point	On the point. 49 22 51 122 52 46.3	FI	W 4s	5.8	5	White cylindrical tower.	Chart:3495 Radar reflector. Year round.				
412.6 <i>G548</i> 2	Croker Island South	49 25 49.2 122 51 47.3	FI(2)	W 6s	5.5	5	White cylindrical tower.	Chart:3495 Flash 0.5 s; eclipse 1 s; flash 0.5 s; eclipse 4 s. Radar reflector. Year round. Chart:3495				

Chart:3495 Edn 03/12 (P12-002)

No.	Name	Position Latitude N. Longitude W.	Light Characteristics		Focal Height in m. above water	Nomi- nal Range	Description Height in meters above ground	Remarks Fog Signals	
				VAN	COU	/ER HA	RBOU	R	
413 G5477	Gosse Point	Off S. shore. 49 17 32.8 122 55 30.5	FI	R	4s	8.6	5	White cylindrical tower, red band at top on 7-pile dolphin.	Radar reflector. Year round. Chart:3495 Edn 02/14 (P14-005) Edn 04/16 (P16-024)
414 G5478	Burns Point	On point, N. side of entrance to Port Moody. 49 17 35.7 122 55 03.9	FI	W	4s	4.6	7	White cylindrical tower, green band at top.	Radar reflector. Year round. Chart:3495
415 <i>G547</i> 9	Carraholly Point	On rock, off point. 49 17 36.7 122 54 30.7	FI	G	4s	4.8	5	White cylindrical tower, green band at top.	Year round. Chart:3495
415.1	Carraholly range	Port Moody. 49 17 43.5 122 53 56.6	F	Y		7.4	10	Square skeleton tower, on 4-pile dolphin, white daymark, red vertical stripe.	Year round.
415.2		277°05' 218m from front.	F	Y		14.8	10	Square skeleton tower, on 4-pile dolphin, white daymark, red vertical stripe.	Year round. Chart:3495 Edn 05/11 (P11-010, 011)
416 <i>G5480</i>	Reed Point	Off S. shore. 49 17 31.8 122 52 25.5	Q	R	1s	9.9	3	Square skeleton tower, on 3-pile dolphin, white rectangular daymark, red band at top.	Year round. Chart:3495
416.5 <i>G5480.4</i>	Port Moody	Entrance to dredged area. 49 17 04.5 122 51 07.7	FI	R	4s	3.2	4	Centre pile on a 5-pile dolphin, red and white triangular daymark.	Year round. Chart:3495